



Highlights:

2 SIP Lines, HD Voice

2 Line Keys

128x48 dot-matrix

Dual Ethernet Ports

Power over Ethernet

RJ9 Headset Interface

EHS Support for Plantronics Headsets

S2P is ideal for both the small office and general enterprise users. Enterprise SIP phone's new design and enhanced features address the need for an elegant IP handset solution for the executive office at a highly competitive price.

S2P is an Internet based voice network phone terminal, which adopts multiple voice control protocols and voice compression coding methods to directly convert analog voice into IP packet for internet transport, thus effectively using the existing bandwidth to provide PSTN quality voice service.

S2P supports SIP protocols, support Bridge, support Router, offers Two Ethernet interfaces and is compatible with various soft switch systems and VoIP voice gateways to provide broadband IP voice service

Generic

- 2 SIP Line
- HD Voice
- POE Enabled
- Handset(HS) / Hands-free(HF) / Headphone(HP) mode (EHS support for Plantronics headsets)
- Desktop / Wall-mount installation
- Optional External Power Supply

Call Features

- Call out / answer / reject
- Mute / Unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer(Attended/Unattended)
- Call Parking / Pick-up (depending on server)
- Redial/Auto-Redial
- Do-Not-Disturb (per line / per phone)
- Auto-Answering (per line)
- Voice Message (on server)
- Local 3-way Conference
- Hot Line
- Hot-Desking

Phone Features

- Phonebook (500 entries)
- Remote Phonebook (XML/LDAP)
- Call log (100 entries, in/out/missed)
- Black/White List Call Filtering
- Voice Message Waiting Indication (VMWI)
- Programmable Soft keys
- Network Time Synchronization
- Action URL / Active URI

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0~7KHz Frequency Response)
- Wideband ADC/DAC 16KHz Sampling
- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
- Wideband CODEC: G.722
- Full-duplex Acoustic Echo Canceller (AEC) – Hands-free Mode, 96ms tail-length
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)

- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Network Features

- 10/100Mbps Ethernet, dual bridged port for PC bypass
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- VLAN
- QoS

Maintenance & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
- Web Management Portal
- Web-based Packet-dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

Physical Features

- LCD: 128x48 dot-matrix
- Keypad: 31 keys, including
- 4 Soft-keys
- 7 Function keys
- 4 Navigation keys + 1 OK key
- 12 Standard Phone Digits keys
- 2 Volume Control keys, Up/Down
- 1 Hands-free key
- HD Hands-free Speaker (0~7KHz) x1
- HD Hands-free Microphone (0~7KHz) x1
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- RJ9 Phone port x2: Handset x1, Headphone x1
- RJ11 EXT port x1: Extension Module x1
- RJ45 Ethernet Port x2: Network x1 (802.3AF POE Class 2Enabled), PC x1 (Bridged to Network)
- Main Chipset: Broadcom
- DC Power Input: 5V / 0.6A
- Power Consumption: Idle ---1.3W, Peak – ~4.3W
- Working Temperature: 0~40°C
- Working Humidity: 10~65%
- Dual-Functional Back Rack x1: Desktop Stand / Wall-mount
- Color: Black
- Package Dimensions: 260x255x62mm (L x W x H)